

# Defoamer

**Harrell's SprayMAX®**

## PRINCIPAL FUNCTIONING AGENTS

Polydimethylsiloxane, Alkylphenoxypoly (Ethoxy) Ethanol .....20.0%

**CONSTITUENTS INEFFECTIVE AS SPRAY ADJUVANT** .....80.0%

**TOTAL** ..... 100.0%

CA Registration No . : 52287-50004-AA

## PRECAUTIONS

Avoid getting in eyes or on skin. Use safety glasses with side shields (or goggles) and water repellent, chemical resistant gloves when handling this product.

Do not contaminate food, feed, seed or water supplies during application or when cleaning equipment.

**IN CASE OF SPILL OR MEDICAL EMERGENCY, CONTACT CHEMTREC 1-800-424-9300.**

## FIRST AID

If on Skin: Wash with soap and water. Consult a physician if any irritation persists

If in Eyes: Rinse with clean water for 15 minutes. Remove contact lenses after the first 5 minutes and continue to rinse. Seek medical attention if irritation persists.

If Ingested: Rinse mouth. Do not induce vomiting. Call 911 or a

physician for treatment advice. Have the product label with you when calling a doctor or going for treatment.

**KEEP OUT OF REACH OF CHILDREN**



## WARNING

Harmful in contact with skin and causes eye irritation.

Read entire label for additional precautionary statements and use directions.

**FOR PROFESSIONAL USE ONLY**



Harrell's, LLC | (800) 282-8007 | Harrells.com

Post Office Box 807 | Lakeland, FL 33802

## NET CONTENTS

1 quart (946 ml)

Weight per quart:

2.11 lbs. @ 68°F

HSMDEF 04/18

# Defoamer

Harrell's Defoamer is a highly active, nonionic, silicone, defoamer designed to eliminate foam in a variety of applications. The use of Harrell's Defoamer can control foaming of spray mixtures. The reduction of foam can reduce mixing and filling times and material loss caused by foaming-over of spray tanks. Harrell's Defoamer formula is designed to prevent foam formation as well as provide curative knock down of foam that has previously formed.

## DIRECTIONS FOR USE:

Shake or agitate before use.

For preventative defoaming: add 1 - 4 ounces of Harrell's Defoamer to a partially water-filled tank first and agitate briefly before adding other products to the water then add remaining water and begin tank mix agitation. Urea water solution may require the higher use rate range for this product. If foaming re-develops after the tank mix level drops, stop agitation and add an additional 1 oz. of Harrell's Defoamer.

For foam reduction while mixing spray solutions: add Harrell's Defoamer at a rate of 1-4 ounces per 100 gallons of spray solution. Water hardness, temperature or tank mix ingredients may require an adjustment up or down in rate. If foaming re-develops after the tank mix level drops, stop agitation and add an additional 1 oz. of Harrell's Defoamer.

## STORAGE AND CONTAINER DISPOSAL

Store above 45°F. Store this product in a dry place, in original container only. Keep lid tightly closed. Keep away from open flame or intense heat. Triple rinse container and offer for recycling or dispose of in accordance with federal, state and local authorities.

## CONDITIONS OF SALE

Seller warrants that products will be labeled as required under state and federal laws and that they conform to the label description. Any non-conformance must be reported in writing to Seller within thirty (30) days after purchase as a prerequisite to maintaining any claim against Seller. Buyer agrees to inspect all products purchased immediately upon delivery. The seller's liability under this warranty is in lieu of all other warranties, expressed or implied, including warranties of merchantability and fitness for a particular purpose. There are no warranties which extend beyond this statement.



Harrell's, LLC  
(800) 282-8007 | Harrells.com  
Post Office Box 807 | Lakeland, FL 33802



HSMDEF 04/18